VALQUA Semiconductor Industry Products

ULTIC ARMOR™-F

High Performance FKM

Product & Benefits

ULTIC ARMOR™–**F** is a high performance FKM material recommended for dynamic locations. Its radical resistance properties make the ULTIC ARMOR™–F suited for CVD, Etch and Ashing applications.



Featured Benefits

- Enhanced Radical Resistance (Weight Loss Ratio and Crack Resistance)
- Anti-Cracking Properties and Low Adhesion to Metal for Dynamic Locations
- Low Metallic Impurities

Applications

- Dry Etch Equipment
- CVD Equipment
- Plasma Ashing Equipment

Contact Us

Valqua America, Inc. 4655 Old Ironsides Dr #380 Santa Clara, CA 95054 www.valqua-america.com

Typical Properties

Color	Midnight Blue
Hardness (Shore A)	67
Tensile Strength (MPa)	12.4
Elongation (%)	140
Modulus 100% Elongation (MPa)	5.4
Maximum Temperature (°C)	200
Compression Set (%)	28

Compression Set: 25% compression at 200℃ for 72 hours Values above are actual measurements, not standards

All trademarks and registered trademarks noted in this file are the exclusive property of Nippon Valqua Industries, Ltd. unless otherwise specified. Although these data are created based on the data and the information (Internal master file No.: VMF104-019) as of April 2019, VALOUA, LTD. may change these data without notice for the reason of improvement in functional of a product, standard revision and others. Please note the following point in use of these data. (1) An operating temperature, pressure range, durability, etc. indicated in this catalogue do not assume each operation conditions but show the application possibility based on our company data, an actual result, etc. Therefore, please use these data after checking the aptitude in actual use environment. (2) The data contained within this catalogue can only be taken as a guide. (3) A standard, a value, etc. are the purposes made legible, and may be performing an extract, recombination, arrangement, conversion, etc. of a value. (4) Although the maximum attention was paid in this data creation, VALQUA, LTD. will not accept responsibility for any loss incurred through error or omission. Please contact your distributor or VALQUA proup if you have any questions.



Valqua America, Inc.

Tel: +1-408-986-1425

Email: info@valqua-america.com

Additional information

ULTIC ARMOR™-F

Performance Properties







